

DUG RADNI VEK PRI SEČENJU METALA

PRO

- 1 Snažna zrna od aluminijum-oksida za dugotrajne performanse
- 2 Matrica od smole za snagu i otpornost na toplotu
- 3 Jaka mreža od fibreglasa ojačava ploču



Video zapis

PRO METAL LEPLJENE REZNE PLOČE

PRO



- Za sečenje metala u opštim metalnim aplikacijama
- Veoma je efikasan za metalce: Dug radni vek
- Projektovano za sečenje metala
- Sa otvorom od 22,23 mm za ugaone brusilice sa standardnom sigurnosnom maticom

KARAKTERISTIKE PROIZVODA						INFORMACIJE ZA PORUČIVANJE				
Unutrašnji prečnik mm	Debljina mm	Specifikacija	Prečnik mm	X-LOCK	oSa	Vrsta pakovanja	Količina u pakovanju	Jedinica pakovanja za dostavu	EAN-kod	Kataloški broj
Sa uvučenim centrom										
22,23	3,0	A 30 S BF	180	-	+	U0	1	25	3165140149389	2 608 600 316
Ravna										
22,23	3,0	A 30 S BF	180	-	+	U0	1	25	3165140149433	2 608 600 321
Sa uvučenim centrom										
22,23	3,0	A 30 S BF	180	-	-	U0	1	20	3165140658584	2 608 603 161
Ravna										
22,23	3,0	A 30 S BF	180	-	-	U0	1	40	3165140658263	2 608 603 167
Sa uvučenim centrom										
22,23	2,5	A 30 S BF	230	-	+	U0	1	25	3165140116466	2 608 600 225
22,23	2,5	A 30 S BF	230	-	-	U0	1	25	4059952631431	2 608 619 776
22,23	3,0	A 30 S BF	230	-	+	U0	1	25	3165140116473	2 608 600 226
Ravna										
22,23	3,0	A 30 S BF	230	-	+	U0	1	25	3165140149495	2 608 600 324
Sa uvučenim centrom										
22,23	3,0	A 30 S BF	230	-	-	U0	1	25	3165140658591	2 608 603 162
Ravna										
22,23	3,0	A 30 S BF	230	-	-	U0	1	25	3165140658270	2 608 603 168
22,23	3,3	A 30 R BF	305	-	+	U0	1	10	3165140252829	2 608 600 649


BOSCH