


DUG RADNI VEK TOKOM SEČENJA DRVETA

EXPERT

- 1 Uz Carbide Technology kompanije Bosch dobijate izuzetnu otpornost
- 2 Dodatni premaz za povećane performanse i izdržljivost



Video zapis



BOSCH

EXPERT WOOD LIST KRUŽNE TESTERE

EXPERT


- Idealan je za sečenje svih vrsta drveta i drvenih kompozita, recimo gazišta stepenica, ukrasnih ploča, dasaka, ploča i svih drugih drvenih radnih površina koje je potrebno seći na radnom mestu
- Najbolje za tesare, stolare, montažere enterijera i građevinske radnike: Dug radni vek
- Traje do 2x duže od Eco for Wood lista kružne testere
- Burgija radi sa ili bez redukcionih prstenova kako bi odgovarala različitim veličinama



KARAKTERISTIKE PROIZVODA

INFORMACIJE ZA PORUČIVANJE

Broj zubaca	Oblik zubaca	NL/prečnik TKS	Prečnik u mm	Otvor mm	Širina sečenja (b1) mm	Debljina mm	Rezni ugao ° α	Ledni ugao ° β	Maks. broj obrtaja (o/min)	Vrsta pakovanja	Količina u pakovanju	Jedinica pakovanja za dostavu	EAN-kod	Kataloški broj
24	ATB	2/7/42	190	30	2	1,3	15	15	10000	C1a	1	1	3165140796491	2 608 644 083
40	ATB	2/7/42	190	30	2	1,3	10	15	10000	C1a	1	1	3165140796507	2 608 644 084
48	ATB	2/7/42	190	30	2	1,3	5	15	10000	C1a	1	1	3165140796514	2 608 644 085
48	ATB	Fastfix	190	FF	2,6	1,6	5	15	10000	C1b	1	1	4059952684826	2 608 902 154
24	ATB		216	30	2,6	1,6	20	13	8800	C1b	1	1	4059952685359	2 608 902 207
48	ATB		216	30	2,6	1,6	10	15	8800	C1b	1	1	4059952685342	2 608 902 206
60	ATB		216	30	2,6	1,6	5	15	8800	C1b	1	1	4059952685366	2 608 902 208
32	ATB	2/7/42	225	30	2,6	1,6	15	15	8400	C1a	1	1	3165140796552	2 608 644 089
48	ATB	2/7/42	225	30	2,6	1,6	10	15	8400	C1a	1	1	3165140796569	2 608 644 090
60	ATB	2/10/60	250	30	2,8	1,8	10	15	7600	C1b	1	1	4059952685632	2 608 902 235
80	ATB	2/10/60	250	30	2,5	1,8	5	15	7600	C1a	1	1	3165140648257	2 608 642 500
22	ATB	2/10/60	250	30	3,2	2,2	20	15	7600	C1b	1	1	4059952684956	2 608 902 167
40	ATB	2/10/60	250	30	3,2	2,2	15	15	7600	C1b	1	1	4059952684963	2 608 902 168
60	ATB	2/10/60	250	30	3,2	2,2	10	15	7600	C1b	1	1	4059952684970	2 608 902 169
80	ATB	2/10/60	250	30	3,2	2,2	5	18	7600	C1b	1	1	4059952684987	2 608 902 170
24	ATB		254	25,4	2,6	1,8	15	15	7500	C1b	1	1	4059952685687	2 608 902 240
40	ATB		254	25,4	2,6	1,8	15	15	7500	C1b	1	1	4059952685694	2 608 902 241
60	ATB		254	25,4	2,6	1,8	10	15	7500	C1b	1	1	4059952685700	2 608 902 242
120	ATB		254	25,4	2,6	1,8	5	15	7500	C1b	1	1	4059952685724	2 608 902 244
40	ATB	2/10/60	254	30	2,4	1,6	15	15	7500	C1b	1	1	4059952685663	2 608 902 238
22	ATB	2/10/60	254	30	2,6	1,8	15	15	7500	C1b	1	1	3165140880909	2 608 644 340
32	ATB	2/10/60	254	30	2,6	1,8	15	15	7500	C1a	1	1	3165140880916	2 608 644 341
54	ATB	2/10/60	254	30	2,6	1,8	10	15	7500	C1b	1	1	3165140880923	2 608 644 342
80	ATB	2/10/60	254	30	2,6	1,8	5	15	7500	C1b	1	1	3165140880930	2 608 644 343
80	ATB	2/10/60	260	30	2,5	1,8	10	15	7300	C1b	1	1	4059952685076	2 608 902 179
100	ATB	2/10/60	300	30	2,5	1,8	5	15	6300	C1a	1	1	3165140648264	2 608 642 501
26	ATB	2/10/60	300	30	3,2	2,2	20	15	6300	C1b	1	1	4059952685083	2 608 902 180
48	ATB	2/10/60	300	30	3,2	2,2	15	15	6300	C1b	1	1	4059952685090	2 608 902 181
60	ATB	2/10/60	300	30	3,2	2,2	10	15	6300	C1b	1	1	4059952685106	2 608 902 182
72	ATB	2/10/60	300	30	3,2	2,2	10	15	6300	C1b	1	1	4059952685113	2 608 902 183
96	ATB	2/10/60	300	30	3,2	2,2	5	18	6300	C1b	1	1	4059952685120	2 608 902 184
54	ATB	2/10/60	350	30	3,5	2,5	15	15	5400	C1b	1	1	4059952685168	2 608 902 188
72	ATB	2/10/60	350	30	3,5	2,5	10	15	5400	C1b	1	1	4059952685175	2 608 902 189


BOSCH